




IPC-615G2-H110 V2.0

Industrial Computer



Support Intel Pentium/Celeron/6-7-8-9th Generation Core i3/5/7 CPU,
LGA1151




Specifications:



Processor	CPU	Intel® Core™ 6th/7th/8th/9th i7 / i5 / i3 / Pentium / Celeron, LGA1151
	Chipset	Intel® H110
Memory	Architecture	Support DDR4 2400
	Capacity	up to 32GB
	DIMM	2 * U-DIMM Slot
Display	DVI	Supports DVI-D with max resolution up to 1920x1200@60Hz
	VGA	Supports max resolution up to 1920x1200@60Hz
	HDMI	Supports max resolution up to 4096x2160@30Hz
	Multi-channel display	Supports asynchronous dual display
Lan	LAN1	Intel GbE LAN controller
	LAN2	Intel GbE LAN controller
Audio	Port	Optional
I/O	COM	4xRS232, 2 x RS232 or RS485
	PS2	1xPS2 Port (Keyboard & Mouse)
	USB	4 x USB3.0, 4 x USB2.0
Other	PCIe	1 x PCIe x16 slot, 1 x PCIe x4 slot , 1 x PCIe x1 slot
	PCI	4 x 32bits PCI slot
	HDD	1 x 2.5" HDD Bay, 1 x 3.5" HDD Bay
	SSD	1 * full size mSATA SSD
	WatchDog	255 seconds programmable
OS	Microsoft Windows	Windows 7/10
	Linux	Ubuntu
Power	Type	ATX
	Power Adapter	AC180~264V
	Power Dissipation	Depending on the CPU (elect 300W , 400W , 500W , 600W , 750W)
Mechanism Parameters	Box structure	Hot dip galvanized sheet steel shel
	Mounting	Desktop installation
	Dimensions (L*W*H)	370mm x 327.5mm x187.2mm
	NW	8.2KG
Environmental	Work Temperature	-20 ~ 60° C (-4°F~140°F) (Using Wide Temperature Grade Solid State Hard Dis)
		0 ~ 45° C (32 °F ~113 °F) (Use normal temperature grade mechanical hard disk)
	Storage Temperature	-40 ~ 80°C (-40°F~185°F)
	Relative humidity	5~95% (No condensation)
	Shake	SSD applied: 1.5 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis
	Shock	SSD applied: 10 G, IEC 60068-2-27, Half-sine wave, 11ms duration
	EMC	CE/FCC Class B
Safety Certification	CCC	

Dimensions :



A: 接地	B: AC 220V	C: 预留串口
D: PS2	E: USB2.0	F: VGA
G: DVI	H: HDMI	I: COM1
J: USB3.0	K: LAN	L: 音频

Ordering Information :

Product Type	Description
IPC-615G2-H110-P300	NO CPU/NO SODIMM/4*RS232/2* (RS232/485) /2×LAN/8×USB2.0(Include 4xUSB3.0)/DVI/VGA/HDMI/4xPCI/3xPCI-E / Power 300W/AC IN 220V / Two-year warranty
IPC-615G2-H110-P400	NO CPU/NO SODIMM/4*RS232/2* (RS232/485) /2×LAN/8×USB2.0(Include 4xUSB3.0)/DVI/VGA/HDMI/4xPCI/3xPCI-E / Power 400W/AC IN 220V / Two-year warranty
IPC-615G2-H110-P500	NO CPU/NO SODIMM/4*RS232/2* (RS232/485) /2×LAN/8×USB2.0(Include 4xUSB3.0)/DVI/VGA/HDMI/4xPCI/3xPCI-E / Power 500W/AC IN 220V / Two-year warranty
IPC-615G2-H110-P600	NO CPU/NO SODIMM/4*RS232/2* (RS232/485) /2×LAN/8×USB2.0(Include 4xUSB3.0)/DVI/VGA/HDMI/4xPCI/3xPCI-E / Power 600W/AC IN 220V / Two-year warranty
IPC-615G2-H110-P750	NO CPU/NO SODIMM/4*RS232/2* (RS232/485) /2×LAN/8×USB2.0(Include 4xUSB3.0)/DVI/VGA/HDMI/4xPCI/3xPCI-E / Power 750W/AC IN 220V / Two-year warranty