

# TPC6000-A122

12.1-inch Intel Bay trail fanless industrial panel PC



Touch Panel PC



## Specifications

### System

Processor : Onboard Intel Bay trail J1900/E3845 quad-core processor, clock 2.0/1.9GHz

Chipset : Intel Bay trail SOC (TDP10W)

Memory : Support DDR3 2G/4G/8G memory

Hard disk : Support SATA 2.5" SSD, HDD and mSATA

Display : Integrated Graphics, support VGA&HDMI

Watchdog : Programmable from 1 to 25 seconds

OS : Win7/Win8/WES7/Linux/Android

### I/O port

LAN : 2 Realtek RTL8111F 1000 Mbps Ethernet port

COM : 6 RS232 (COM1, COM5 and COM6 optional RS485)

USB : 1 USB 3.0 and 3 USB2.0 ports

Speaker : Built-in small Speaker

Expansion : 1 Mini-PCIe slots, scalable 3G, Wifi card

Other I/O : Power switch, DC IN, HDMI, VGA

### LCD

Size / Type : 12.1" TFT LCD

Resolution : 800x600 (optional 1024x768)

Backlit : LED with MTBF 50000 hours (800x600)

: LED with MTBF 30000 hours (1024x768)

Brightness : 300cd/sqm (optional 350cd/sqm)

Display area : 246x184.5mm

### Institutional

Front Panel : Aluminum-magnesium alloy die-casting, cover with PET film, IP65 degree of protection

Box structure : High-strength sheet metal structure, high temperature paint handling

Cooling mode : Large area designed finned heat sinks

Mounting : Supports Panel and VESA mounting

Overall size : 321x242.8x78mm (WxHxD)

Case Size : 301x227x72mm (WxHxD)

Hole Size : 304x230mm (WxH)

Weight : 3.74kg

### Touch screen

Size / Type : 12.1 inch and High temperature five-wire resistive screen

Resolution : 4096x4096

Click life : 250g efforts, 35 million times

Draw life : 250g efforts, 5 million times

Transmittance : More than 81%

### Power and Environmental

Working tem. : 0~+50°C (Electronic disk)

Storage tem. : -30~+70°C

Relative humidity : 10~95%@40°C (No condensation)

Vibrating : 50~500Hz, 1.5G, 0.15mm Peak to peak

Shock : 10G/peak (11ms sec)

Power in : DC 12V

Consumption : 21 watt

